

POWERFENCE FENCING SYSTEM

Ideal for renovators, because of the lightweight panels and simple construction method, PowerFence uses standard 1800 x 600 x 75mm PowerPanels, steel brackets and steel posts which can be easily and quickly erected without the need for excavation or strip footing. Ideal for houses, multi-residential projects, low-rise apartments and DIY projects.

POWERFENCE STANDARD PANEL SIZES

75mm thick x 600mm wide x 1800mm and 2400mm long.

FENCING - HOUSES & LOW RISE MULTI RESIDENTIAL

- easy to build, cost effective and attractive
- can be easily painted or fully rendered
- creates privacy and acts as a reflective noise barrier
- perfect for boundary fencing or as an alternative to standard masonry front fences
- can change the edge profiles (monolithic or expressed) to create a range of looks with capping, finishes and routing patterns

HEBEL POWERFENCE PROVIDES AN INNOVATIVE SOLID FENCING SYSTEM THAT'S ATTRACTIVE, VERSATILE AND EASY TO INSTALL.



| ITEM | DESCRIPTION | LOCATION |
|------|---|--|
| 1 | Hebel PowerFence panel | Entire fence |
| 2 | PowerFence Bracket Set | Lateral support for panels |
| 3 | Screw 10-24 x 40 self drilling | To fix bracket to post and post cover to post |
| 4 | PowerFence Post | Structural post for PowerFence |
| 5 | PowerFence Post Extension Piece 800mm | Post extension for PowerFence Post (300mm insertion) |
| 6 | PowerFence Post Cover 115 x 1800 x 15mm | Vertical express FC post cover - end and internal corners |
| 7 | PowerFence Post Cover 240 x 1800 x 15mm | Vertical express FC post cover - common posts and external corners |
| 8 | Hebel Capping - 50mm Hebel PowerBlock (pack of 6) | Caps top of posts or panels |
| 9 | Deflection Head 76mm x 50mm x 3m x 0.8mm BMT | Caps top of PowerFence panels |
| 10 | Hebel Adhesive | Used for all panel joints |
| 11 | Hebel Anti - Corrosion Paint 500ml | Used to coat exposed reo on cut panels |

THE HEBEL POWERFENCE BRACKET

Multi-purpose and adjustable for all-round easier and safer construction. Move it up or down while constructing. Rotate it to make a corner. Turn it upside down for a starting cleat. Use it as a lateral support for all the panels. Separate its two integrated sections for stepped or terraced fencing. Easy to position and refix as you go.



For more information contact 1300 369 448 www.hebel.com.au

CSR