
HEBEL POWERPANEL⁵⁰ INTERTENANCY WALL SYSTEMS

SIMPLE AND EASY TO INSTALL. CODEMARK FOR EASY COMPLIANCE



PROVEN

Hebel PowerPanel⁵⁰ has been developed and tested for low rise multi-residential intertenancy wall systems, which are warranted by CSR.



POWERPANEL⁵⁰ INTERTENANCY / PARTY WALL

The PowerPanel⁵⁰ Intertenancy Wall System consists of 50mm thick steel reinforced AAC panels installed vertically to timber or steel frame. Uses aluminium wall brackets for discontinuous construction and Hebel deflection head track for base connection.

- **Fire rating:** Up to 90/90/90
- Acoustic: Achieves R_w + C_{tr} 50 dependent on wall system configuration

Note: Refer to Hebel website or or contact Hebel Technical services for further details on performance of wall system.

POWERPANEL⁵⁰ STANDARD PANEL SIZES

50mm thick x 600mm wide x 2400mm, 2550mm, 2700mm, 2850mm and 3000mm long.

POWERPANEL⁵⁰ INTERTENANCY / PARTY WALLS - LOW RISE MULTI RESIDENTIAL

- Fast and easy system to install
- Easy to fire-rate with no need for fire-rated plasterboard between floor levels at joists and in roof space
- Narrow system wall width starting at 230mm with 70mm separation between stud frames across all systems
- Simple system componentry maximises construction efficiency
- Panels up to 3 metres in height installed vertically
- Easy to cut PowerPanel⁵⁰ panels onsite
- PowerPanel⁵⁰ wall construction not affected by wet or damp conditions
- Minimal onsite waste
- Environmentally responsible building material





HEBEL POWERPANEL⁵⁰ INTERTENANCY WALL SYSTEMS

5C

6


7

Screw 10 - 16 x 16mm Hex Head self drilling / bracket

Aluminium Brackets (75 x 50 x 40mm)

Deflection Head Track (3m lengths)

SIMPLE AND EASY TO INSTALL. CODEMARK FOR EASY COMPLIANCE



Fixing Aluminium Bracket to Hebel Fixing Aluminium Bracket to steel frame

Ground floor panels Panels on upper level & between trusses

Only at base of wall