




# HEBEL INTERTENANCY WALLS FOR MAXIMUM FLOOR SPACE WITH CONCEALED SERVICES ON ONE SIDE CSR21070 - CSR21071



VERTICAL CROSS SECTION DETAIL A-A



DETAIL PLAN VIEW



ISOMETRIC VIEW

NTS

INTERTENANCY WALL									
CODE	APPLICATION	WALL THICKNESS	WALL HEIGHT 'H'	FRL (B)	R <sub>w</sub> +C <sub>v</sub> (C)	SYSTEM COMPONENT VARIATIONS			
						LINING A	MIN. GAP	INSULATION (A)	LINING B
CSR21070	DRY TO DRY	185mm	UP TO 3.3m HIGH	-/90/90 FOR WALL HEIGHTS UP TO 3.3m	50	13mm GYPROCK CD	20mm	75mm BRADFORD ACOUSTIGARD 11	13mm GYPROCK CD
CSR21071	DRY TO WET	185mm	UP TO 3.3m HIGH	-/90/90 FOR WALL HEIGHTS UP TO 3.3m	50	13mm GYPROCK CD	20mm	50mm BRADFORD ACOUSTIGARD 11	13mm AQUACHEK

REFER TO DESIGN AND INSTALLATION GUIDES FOR HIGH RISE INTERTENANCY AND SERVICE WALLS (HEB 1354) FOR MORE CONSTRUCTION AND PRODUCT INFORMATION. 13mm AQUACHEK CAN BE REPLACED BY 9mm FIBRE CEMENT SHEETING AND ACHIEVE THE SAME FRL AND ACOUSTICS. FOR WALLS > 3.3m AND ≤ 4.65m, CAGED TONGUE & GROOVE POWEROANEL CAN BE USED AND WILL ACHIEVE A FRL OF -/120/120. REFER TO DESIGN AND INSTALLATION GUIDES FOR SHAFT AND SCISSOR STAIR WALLS (HELIT 032) FOR MORE DETAILED INFORMATION.

<b>CSR BUILDING PRODUCTS LTD</b> Head Office: Trinitis 3, 39 DELHI RD, NORTH RYDE NSW 2113 LOCKED BAG 1345, NORTH RYDE BC NSW 1670 A.B.N. 55 008 631 356 Ph: 1300 369 448 www.hebelaustralia.com.au	<b>hebel</b> The better way to build CSR Building Products Limited A.B.N. 55 008 631 356	SYSTEM CODE	TITLE		
		CSR21070 - 21071	HEBEL CORRIDOR WALLS		
DESIGN GUIDE REFERENCE	SCALE	SHEET SIZE	DRAWN	DATE	
---	1:5 @ A3	A3	ET	12.04.24	
		SHEET NO	CHECK	REVISION	
		1 of 1	CW	D	